

MOLY 29 *Open Gear Grease*

Carter Open Gear Grease

Utilizing Molybdenum Disulfide, Moly 29 (Carter Open Gear Grease) provides superior anti-wear characteristics, extending the life of open gears. This highly adhesive product comes in convenient cartridges for use in caulking guns. While many other open gear lubricants contain solvents requiring evaporation, Moly 29 (Carter Open Gear Grease) is solvent free. Gears lubricated with this product are ready for immediate use.

Features

- Highly adhesive, tacky
- Highly cohesive
- Moisture resistant
- Solvent free

Performance

- Assure government compliance
- Protects gears against wear
- Protects against corrosion
- Reduces personnel and property hazards

Typical Properties

Product Code #	200022	Appearance	Black
Unworked Penetration	285 – 305	Texture	Smooth, Tacky
NLGI Grade	2	Timken OK Load, Lbs.	40
Thickener	Inorganic	4-Ball Wear Test ASTM D-2266	
Dropping Point, °F	None	40 kg., 1200 RPM, 167°F,	
Base Oil Properties,		1 hr., Scar diam. mm.	0.84
SUS @ 210°F	3000	Operating Range, °F	+25 to 400
Flash Point, °F, PM	378		

Revised 11/06 WHC

TOTAL Lubricants USA, Inc.

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2002 All rights reserved.

Linden, NJ 07036
5 North Stiles Street
908.862.9300 800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198